



**WaterSense[®] Specification for Weather-Based
Irrigation Controllers**

Version 1.0

November 3, 2011

WaterSense® Specification for Weather-Based Irrigation Controllers

1.0 Scope and Objective

This specification establishes the criteria for weather-based irrigation controllers labeled under the U.S. Environmental Protection Agency's (EPA's) WaterSense program. It applies to stand-alone controllers, add-on devices, and plug-in devices (collectively referred to in this specification as controllers) that use current weather data as a basis for scheduling irrigation. This specification applies to controllers that create or modify irrigation schedules based on evapotranspiration (ET) principles by:

- Storing historical crop evapotranspiration (ETc) data characteristics of the site and modifying these data with an onsite sensor;
- Using onsite weather sensors as a basis for calculating real time ETc;
- Using a central weather station as a basis for ETc calculations and transmitting the data to individual users from remote sites; or
- Using onsite weather sensors.

For the purpose of this specification, the onsite weather sensor requirement includes weather sensors such as temperature or solar radiation. Because rainfall devices do not modify ETc but interrupt or modify irrigation events based on rainfall, they do not meet this onsite weather sensor requirement when used as the sole method for modifying irrigation schedules.

The performance criteria contained in this specification are designed to test the capability of the controller to provide adequate and efficient irrigation while minimizing potential runoff when the controller is programmed and operated in compliance with the manufacturer's instructions. Conformance with these requirements is an indication that the controller has the capacity to modify or generate appropriate irrigation schedules based on weather inputs.

This specification applies to controllers for use in residential or commercial landscape irrigation applications.

2.0 Summary of Criteria

Controllers must meet criteria in the following areas, as applicable:

- Irrigation adequacy for each zone shall be greater than or equal to 80 percent as specified in Section 3.0.
- Irrigation excess for each zone shall be less than or equal to 10 percent as specified in Section 3.0. The average of the irrigation excess scores calculated across the six zones shall be less than or equal to 5 percent as specified in Section 3.0.
- The controller must conform to the supplemental capability requirements specified in Section 4.0.

3.0 Performance Criteria

The controller, as configured for testing in accordance with Appendix A, shall be tested in accordance with the eighth draft of the Smart Water Application Technologies™ (SWAT) test protocol for climatologically based controllers included in Appendix C, with the additional requirements listed in Section 3.1, and shall meet the performance criteria in Section 3.2.

In accordance with the SWAT protocol, the test period shall be 30 consecutive days. However, the test may run past the initial 30 days until a 30-day period occurs where all conditions in Section 3.1 are met. The first valid 30-day test period shall be used to calculate irrigation adequacy and irrigation excess. If the thresholds included in Section 3.2 are not met, the test shall be restarted.

3.1 Testing Modifications to the SWAT Protocol¹

- 3.1.1 **Minimum Runtimes:** All runtimes (irrigation cycles) that occur during the test period must be greater than three minutes in duration. Water applied during irrigation events totaling three minutes or less shall be excluded from the daily water balance calculation.
- 3.1.2 **Missing Data From the Reference Weather Station:**
 - 3.1.2.1 For the test to be valid, there shall be no more than two consecutive days, or no more than three days in total, of missing reference evapotranspiration (ET_o) data generated by the reference weather station during the test period.
 - 3.1.2.1.1 If ET_o data generated by the reference weather station are missing during the test, then the previous day's ET_o data shall be used instead.
 - 3.1.2.2 There shall be no missing rainfall data during the test period; however, data from a backup rain gauge located at the same site as the reference weather station may be substituted for missing rainfall data. If data from a backup rain gauge are available, this is not considered missing data.
- 3.1.3 **Rainfall Requirement:** There shall be at least four individual days during the test period with 0.10 inches or greater of gross rainfall for the test to be considered valid. These individual day rainfall amounts count toward the total rainfall requirement specified in the SWAT protocol.
- 3.1.4 **Order of Operations:** The order of operations implemented during the SWAT protocol daily water balance calculation shall be ET_c , irrigation, then rainfall. This differs from the order as designated in the SWAT protocol where rainfall occurs first.

3.2 Performance Requirements

¹ WaterSense has prepared and will make available software that performs SWAT protocol calculations with these modifications.

- 3.2.1 Irrigation adequacy, as calculated in accordance with the SWAT protocol modified by Section 3.1 of this specification, shall be greater than or equal to 80 percent for each zone.
- 3.2.2 Irrigation excess, as calculated in accordance with the SWAT protocol modified by Section 3.1 of this specification, shall be less than or equal to 10 percent for each zone. The average of the irrigation excess scores calculated across the six zones shall be less than or equal to 5 percent.

4.0 Supplemental Capability Requirements

The controller, as configured for testing in accordance with Appendix A, shall have the following supplemental capabilities in both smart mode and standard mode.

- 4.1 The controller shall be capable of preserving the contents of the irrigation program settings when the power source is lost and without relying on an external battery backup.
- 4.2 The controller shall either be capable of independent, zone-specific programming or storing a minimum of three different programs to allow for separate schedules for zones with differing water needs.
- 4.3 The controller shall be capable of indicating to the user when it is not receiving a signal or local sensor input and is not adjusting irrigation based on current weather conditions.
- 4.4 The controller shall be capable of interfacing with a rainfall device.
- 4.5 The controller shall be capable of accommodating watering restrictions as follows:
 - 4.5.1 Operation on a prescribed day(s)-of-week schedule (e.g., Monday-Wednesday-Friday, Tuesday-Thursday-Saturday; any two days; any single day, etc.).
 - 4.5.2 Either even day or odd day scheduling, or any day interval scheduling between two and seven days.
 - 4.5.3 The ability to set irrigation runtimes to avoid watering during a prohibited time of day (e.g., between 9:00 a.m. and 9:00 p.m.).
 - 4.5.4 Complete shutoff (e.g., on/off switch) to accommodate outdoor irrigation prohibition restrictions.
- 4.6 The controller shall include a percent adjust (water budget) feature.²
- 4.7 If the primary source of weather information is lost, the controller shall be capable of reverting to either a proxy of historical weather data or a percent adjust (water budget) feature.

² The percent adjust (water budget) feature is defined as having the means to increase or decrease the runtimes or application rates for zones by means of one adjustment without modifying the settings for each individual zone.

- 4.8 The controller shall be capable of allowing for a manual operation troubleshooting test cycle and shall automatically return to smart mode within some period of time as designated by the manufacturer, even if the switch is still positioned for manual operation.

5.0 Packaging and Product Documentation Requirements

Controllers shall be packaged and provided with documentation as indicated in this section.

5.1 General: Applies to Stand-Alone, Add-On Devices, and Plug-In Devices

The product, as packaged, shall include the same components (excluding the base controller for add-on or plug-in devices) or attributes that it was tested with to meet the requirements of this specification. For controllers with weather stations, sensors, or rainfall devices, all components tested with the controller must be packaged with the controller. For signal-based controllers, instructions on acquiring the proper weather signal shall be packaged with the controller.

The product packaging shall include an instruction manual that lists the settings and specific parts used during the performance test described in Section 3.0. The instruction manual shall also include the maximum number of stations for the product.

The product shall not be packaged nor marked to encourage operation of the controller in standard mode. Any instruction related to the maintenance of the product shall direct the user on how to return the controller to smart mode.

5.2 Add-on Devices

The add-on device is not required to be packaged with the base controller(s) that it was tested with to meet the requirements of this specification. However, the product documentation for the add-on device must list each base controller model with which the device was tested and demonstrated to meet the requirements of this specification and with which the manufacturer intends it to be connected. The documentation must also contain a statement to the effect that the device is only WaterSense labeled when used in combination with a base controller on the provided list.

5.3 Plug-in Devices

The plug-in device is not required to be packaged with the base controller(s) that it was tested with to meet the requirements of this specification. However, the product documentation for the plug-in device must list each base controller model with which the device was tested and demonstrated to meet the requirements of this specification and with which the manufacturer intends it to be connected. The documentation must also contain a statement to the effect that the device is only WaterSense labeled when used in combination with a base controller on the provided list.

6.0 Effective Date

This specification is effective as of November 3, 2011.

7.0 Future Specification Revisions

EPA reserves the right to revise this specification should technological and/or market changes affect its usefulness to consumers, industry, or the environment. Revisions to the specification shall be made following discussions with industry partners and other interested stakeholders.

8.0 Definitions

Definitions within the SWAT test protocol for climatologically based controllers (Draft 8, September 2008) are included by reference.

Add-on device: A product that modifies an existing system equipped with a standard clock timer controller to use current weather data as a basis for controlling the irrigation schedule. For purposes of this specification, add-on devices are defined as those that are designed to work with any brand of base controller and may connect through a variety of ways.

Base controller: The standard clock timer controller to which the add-on or plug-in device is attached for full operation.

Plug-in device: A product that modifies an existing system equipped with a standard clock timer controller to use current weather data as a basis for controlling the irrigation schedule. For purposes of this specification, plug-in devices are defined as those that are designed to work specifically with one brand of controller and may connect with the base controller through a variety of ways.

Rainfall device: A device that either senses or measures rainfall to reduce or interrupt irrigation in response to rain events. For the purpose of this specification this includes, but is not limited to, rainfall interrupt devices and tipping bucket rain gauges.

Reference weather station: The weather station maintained by the licensed certifying body that produces the reference weather data used during the performance test.

Smart mode: The operating mode in which the controller is using weather data to schedule irrigation or modify the irrigation schedule.

Stand-alone controller: A product for which weather-based control is an integrated capability. This includes a single controlling device (i.e., the irrigation controller) and all of the sensors and/or weather service(s) that provide the weather data.

Standard mode: The operating mode in which the controller is not using weather data to schedule irrigation or modify the irrigation schedule (i.e., when a weather-based controller is not in smart mode).

APPENDIX A: Testing Configuration and Programming

Controllers shall be configured for testing in accordance with the relevant sections below.

1.0 General: Applies to Stand-Alone, Add-on Devices, and Plug-in Devices

The controller shall be tested with all weather stations, sensors, rainfall devices, or service(s) required to meet this specification.

The controller shall be programmed according to the list of settings provided by the manufacturer in the product's instruction manual described in Section 5.1 of this specification.

2.0 Add-on Devices

Add-on devices must be tested with each base controller model with which the manufacturer intends it to be connected in order to meet the requirements of this specification. As a unit, the add-on device and the base controller must meet all of the requirements contained in this specification.

3.0 Plug-in Devices

Plug-in devices must be tested with each base controller model with which the manufacturer intends it to be connected in order to meet the requirements of this specification. As a unit, the plug-in device and the base controller must meet all of the requirements contained in this specification.

APPENDIX B: Informative Annex for WaterSense Labeling

The following requirements must be met for products to earn the WaterSense label.

1.0 WaterSense Partnership

The manufacturer of a controller must have a signed partnership agreement in place with EPA. Manufacturers of components, such as weather stations or additional sensors, or weather services are not eligible for partnership on that basis alone.

2.0 Conformity Assessment

Conformance to this specification must be certified by a licensed certifying body accredited in accordance with the WaterSense Product Certification System.

3.0 WaterSense Labeling

- 3.1 The label can be applied to product packaging that includes the certified controller and all components (excluding the base controller for add-on and plug-in devices) or attributes with which the controller was tested to meet the requirements of this specification.
- 3.2 For add-on devices, only the devices certified to meet the requirements of this specification may bear the WaterSense label. Base controllers with which the add-on devices are tested and that are sold separately from the add-on devices shall not bear the WaterSense label. Product documentation shall indicate that the add-on device is only WaterSense labeled when used in combination with the base controller(s) listed in product documentation described in Section 5.0 of this specification.
- 3.3 For plug-in devices, only the devices certified to meet the requirements of this specification may bear the WaterSense label. Base controllers with which the plug-in devices are tested and that are sold separately from the plug-in devices shall not bear the WaterSense label. Product documentation shall indicate that the plug-in device is only WaterSense labeled when used in combination with the base controller(s) listed in product documentation described in Section 5.0 of this specification.

4.0 Product Sampling for Certification

One product shall be selected at random from the entire inventory of the manufacturer's packed production.

APPENDIX C

Smart Water Application Technologies™ (SWAT)

Turf and Landscape Irrigation System Smart Controllers

CLIMATOLOGICALLY BASED CONTROLLERS

8th Testing Protocol (September 2008)

Developed by the



SWAT Committee
6540 Arlington Blvd
Falls Church, VA 22048-6638
www.irrigation.org



TABLE OF CONTENTS

FOREWARD	i
INTRODUCTION	ii
1.0 Scope	1
2.0 Normative References	1
3.0 Definitions	1
4.0 Test Methods	4
4.1 Sampling	4
4.2 General	4
4.3 Test for Adequacy, Efficiency and Runoff Potential	5
4.4 Related Considerations	8
4.5 Test Report	8
4.6 Test Duration	9
4.7 Weather Data Source	9
4.8 Onsite Weather Collection Devices	9
5.0 Normative Annex	10
6.0 Informative Annex	12

FOREWORD

The Irrigation Association has established a Smart Water Application Technologies™, or SWAT, committee to oversee the development of product testing protocols. This committee is assisted by a Technical Working Group (TWG) and project leaders. The protocol development process involves a drafting of the document followed by a public review and comments period. If required, the document is redrafted and a second review process is initiated. Ultimately the SWAT committee votes on the acceptability of the last protocol. All protocols will be reviewed for possible revision every three years. The development of this testing protocol represents the first attempt by the Irrigation Association to develop product testing protocols. The actual product testing began in 2004 when the first commercial controller was tested using the 5th Draft Testing Protocol dated May 3, 2004. The documents have no known predecessors.

This protocol was developed to test products designed and sold for use at homes and similar scale light commercial and institutional properties. This protocol may not be suitable for testing products used in larger more demanding irrigation systems used at parks, golf courses, etc.

This testing protocol consists of the following parts under the general title of “Turf and Landscape Irrigation System Smart Controllers.”

Climatologically Based Controllers

Another protocol addresses the following parts under the general title of “Turf and Landscape Irrigation System Smart Controllers.”

Soil Moisture Sensor Based Controllers

Phase 1: Indoor lab screening tests

Phase 2: Operational test on a virtual landscape

INTRODUCTION

This protocol provides a procedure for characterizing the efficacy of irrigation system controllers that utilize climatological data as a basis for scheduling irrigations. They may also use on-site temperature or rainfall sensors. This evaluation concept requires the use of accepted formulas for calculating crop evapotranspiration (ET_c). Commercial versions of this type of controller include the following:

- Controllers that store historical ET_c data characteristic of the site
- Controllers that utilize on-site sensor as a basis for calculating real time ET_c
- Controllers that utilize a central weather station as a basis for ET_c calculations and to transmit the data to individual home owners from remote sites
- Controllers that utilize on-site rainfall and temperature sensors
- Control technology that is added on to existing time based controllers

It is recognized that controlling the irrigation of turf and landscape is a combination of scientific theory and subjective judgments. The attempt in developing this protocol is to use only generally recognized theory and to avoid judgments involving the art of irrigation. The protocol then recognizes that only the theory of irrigation is controllable by the skill of the controller manufacturer. The protocol will measure the ability of the controllers to provide adequate and efficient irrigation while minimizing potential run-off.

The concept of climatologically controlling irrigation systems has an extensive history of scientific study and documentation. The objective of this protocol is to evaluate how well current commercial technology has integrated the scientific data into a practical system that meets the agronomic needs of the turf and landscape plants.

In general there are at least two types of standards. The first is a standard that defines the details of how a performance test is to be conducted and what data will be recorded. This Smart Water Application Technologies™ testing protocol is that type of test. It does not result in a pass or fail evaluation. The second type of standard defines performance limits that must be met to quantify the capabilities of the product. The performance standards in this case are established by related considerations and organizations.

In order to realize the full potential of the smart controller concept the following issues must be addressed:

- The quality of the input data must be verified by a certified professional
- The controller must be set up and programmed by individuals familiar with the technology
- The irrigation system must be properly designed and maintained

Turf and Landscape Irrigation System Smart Controllers – Climatologically Based

1.0 Scope

This evaluation will be accomplished by creating a virtual landscape subjected to a representative climate and to evaluate the ability of individual controllers to adequately and efficiently irrigate that landscape. The individual zones within the landscape will represent a range of exposure, soil types and agronomic conditions. As a standard from which to judge the controller's performance, a detailed moisture balance calculation will be made for each zone. The total accumulated deficit over time will be a measure of the adequacy. The accumulated surplus of applied water over time will be a measure of system efficiency. Water applied beyond the soil's ability to absorb it will be characterized as runoff, further degrading the application efficiency. The study will use ASCE-EWRI data from a representative accredited weather station. Further the study is not meant to include individualized water management strategies aimed at producing special physiological affects. If the controller maintains root zone moistures at the levels specified, the protocol assumes that the crop growth and quality will be adequate. The moisture balance calculation will assume that the plant materials are functioning as mature plants.

2.0 Normative References

The Environmental and Water Resource Institute (EWRI) of the American Society of Civil Engineers, study on the standardization of reference Evapotranspiration (ET_o) formulas. See <http://www.kimberly.uidaho.edu/water/asceewri/>

3.0 Definitions

For the purposes of this IA Standard, the following definitions apply:

3.1 Allowable Surface Accumulation (ASA)

Free standing water created on top of the soil surface by application rates that exceed soil intake rates that is generally restrained from running off by the combined effects of surface detention and the presence of the crop canopy, thatch layer, or accumulated vegetative waste.

3.2 Crop (Turf) Coefficient (K_c)

Coefficients as determined for specific crops that relate ET_o to ET_c as follows:

$$ET_c = K_c (ET_o)$$

This provides a convenient method for calculating ET_c when field data is not available.

3.3 Crop Evapotranspiration (ET_c)

Specific crop moisture requirements as determined by lysimeter studies or calculated by formulas

3.4 Evapotranspiration (ET)

Water transpired by vegetation plus that evaporated from the soil

3.5 Field Capacity

The amount of water remaining in the soil after the soil has been saturated and allowed to drain away

3.6 Landscape Coefficient (K_L)

A functional equivalent of the crop coefficient for turf that integrates the effects of species factor (k_s), density factor (k_d) and microclimate factor (k_{mc}) for landscapes.

$$K_L = (k_s) (k_d) (k_{mc})$$
$$ET_c = K_L (ET_o)$$

3.7 Permanent Wilting Point

The largest content of water in a soil at which plants will wilt and not recover when placed in a humidity chamber

3.8 Reference Evapotranspiration (ET_o)

Estimates of crop evapotranspiration as calculated using climatological information and accepted formulas. See: ASCE-EWRI, Ref. 5.2.

3.9 Root Zone Working Water Storage (RZWWS)

A root zone water storage value that integrates the effects of actual root zone depth, soil moisture storage capacity, and allowable moisture depletion

3.10 Precipitation Rate (PR)

The amount of irrigation water applied per unit of time.

3.11 Smart Controller

Smart controllers estimate or measure depletion of available plant soil moisture in order to operate an irrigation system, replenishing water as needed while minimizing excess water use. A properly programmed smart controller requires initial site specific set-up and will make irrigation schedule adjustments, including run times and required cycles throughout the irrigation season without human intervention.

3.12 Soak Time

The time required for a given application to infiltrate into the root zone.

3.13 Zones

A portion of the system connected to a common water supply and intended to operate at the same time

3.14 Direct Runoff

Water applied that exceeded the maximum allowable runtime

3.15 Soak Runoff

Runoff losses attributable to scheduling multiple irrigation cycles without allowing sufficient soak time between cycles

3.16 Effective (Net) Irrigation

Water applied that was added to the root zone working storage and usable by the crop

3.17 Deficit

Required water that was not available in the root zone working storage

3.18 Surplus

Water applied in excess of the root zone working storage

3.19 Irrigation Adequacy

Ratio of crop ETc less deficit over crop ETc as a percentage

3.20 Scheduling Efficiency

Ratio of net irrigation less scheduling losses over net irrigation as a percentage

3.21 Net (Effective) Rainfall

Portion of total rainfall which becomes available for plant growth

3.22 Rainfall Efficiency

Ratio of the rainfall stored in the root zone over the net rainfall as a percentage

4.0 Test Methods**4.1 Sampling**

A representative of the testing laboratory will select test specimen for each test at random from a sample of at least 10 units supplied by the manufacturer. The testing agency will retain the controller.

4.2 General

System controllers will be installed at the test site complete with sensors and/or communication links. The controller output will be connected to 6 zone relays representing the control valves of the virtual yard. A data logger will be connected to the 6 zone relays. The data logger will record valve open and closing events. Valve run times will be used with application rate and efficiency data to provide the net irrigation application. This data is used in the moisture balance calculation.

Develop a day-by-day moisture balance calculation using the actual valve run times taken from the data logger. Calculate the system performance parameters as required to summarize the controller's performance including:

- Gross irrigation
- Direct runoff
- Soak runoff
- Effective irrigation
- Deficit
- Surplus
- Irrigation adequacy

- Scheduling efficiency
- Application efficiency
- Rainfall efficiency

4.3 Test for Adequacy, Efficiency and Runoff Potential

Communicate with the controller manufacturers the starting date of the test run, the source of the real time weather data, and the on-site weather data history.

Communicate with the controller manufacturers the definitions of the virtual yard as given in Table 1.

Table 1: Description of Zones

Item No.	Description	Zone #1	Zone #2	Zone #3	Zone #4	Zone #5	Zone #6
1	Soil Texture (1)	Loam	Silty Clay	Loamy Sand	Sandy Loam	Clay Loam	Clay
2	Slope, %	6	10	8	12	2	20
3	Exposure	75% Shade	Full Sun	Full Sun	50% Shade	Full Sun	Full Sun
4	Root Zone Working Water Storage (RZWWS), in. (2)	0.85	0.55	0.90	2.00	2.25	0.55
5	Vegetation	Fescue (Tall)	Bermuda	Ground Cover	Woody Shrubs	Trees & Ground Cover	Bermuda
6	Crop (Turf) Coefficient (K_c)	See Table 2	See Table 2	N/A	N/A	N/A	See Table 2
7	Landscape Coefficient (K_L) (3)	N/A	N/A	0.55	0.40	0.61	N/A
8	Irrigation System	Pop-Up Spray Heads	Pop-Up Spray Heads	Pop-Up Spray Heads	Pop-Up Spray Heads	Surface Drip	Rotors
9	Precipitation Rate (PR), in./h	1.60	1.60	1.40	1.40	0.20	0.35
10	Estimated Application Efficiency, %	55	60	70	75	80	65
11	Gross Area, ft ² (4)	1,000	1,200	800	500	650	1,600

(1) See Table 3 for soil intake rate

(2) Root Zone Working Water Storage (RZWWS) calculations:

Item No.	Description	Zone #1	Zone #2	Zone #3	Zone #4	Zone #5	Zone #6
1	Vegetation	Fescue	Bermuda	Ground cover	Woody shrubs	Trees & ground cover	Bermuda
2	Soil Texture	Loam	Silty clay	Loamy sand	Sandy loam	Clay loam	Clay
3	Allowable Depletion	50	40	50	55	50	35
4	Available Water, in./in.	0.17	0.17	0.09	0.13	0.18	0.17
5	Root Zone Depth, in.	10.0	8.1	20.0	28.0	25.0	9.2
6	Root Zone Working Water Storage, in.	0.85	0.55	0.90	2.00	2.25	0.55

- (3) Landscape coefficients work-up from section 6.0 Informative Annex, item 6.3

Parameter	Zone 3	Zone 4	Zone 5
k_s	0.5	0.5	0.5
k_d	1.0	1.0	1.1
k_{mc}	1.1	0.8	1.1
K_L	0.55	0.40	0.61

The protocol uses a simplified treatment of Zones 3, 4 and 5 where complete wetting of the surface area may not be required. A more studied analysis may be appropriate where high value vegetation is irrigated in drier climates.

- (4) Area as defined by extent of vegetative planting. Make no allowance for geometrically complex boundaries.

Provide crop (turf) coefficients. See Table 2.

Table 2: Crop (Turf) Coefficients (Kc)

Month	Full Sun		75% Shade	
	Fescue	Bermuda	Fescue	Bermuda
January	0.61	0.52	0.41	0.35
February	0.69	0.64	0.46	0.43
March	0.77	0.70	0.52	0.47
April	0.84	0.73	0.56	0.49
May	0.90	0.73	0.60	0.49
June	0.93	0.71	0.62	0.48
July	0.93	0.69	0.62	0.46
August	0.89	0.67	0.60	0.45
September	0.83	0.64	0.56	0.43
October	0.75	0.60	0.50	0.40
November	0.67	0.57	0.45	0.38
December	0.59	0.53	0.40	0.36

- (1) As modified from Table A.1 Ref: 5.4
 (2) The Kc values in this table are meant to be representative for test purposes only. They should be verified before being accepted in specific locations.

Provide basic soil intake rate and allowable surface accumulation for the soil textural classes and field slopes as shown in Table 3.

Table 3: Basic Soil Intake Rate (IR) and Allowable Surface Accumulation (ASA) as it Relates to Soil Textural Class (1) and Slope

Soil Textural Class	Basic Soil Intake Rate in./h (IR)	Allowable Surface Accumulation (ASA) in.			
		Slope, 0 to 3%	Slope, 4 to 6%	Slope, 7 to 12%	Slope, 13% <
Clay	0.1	0.2	0.15	0.1	0.1
Silty Clay	0.15	0.23	0.19	0.16	0.13
Clay Loam	0.2	0.26	0.22	0.18	0.15
Loam	0.35	0.3	0.25	0.21	0.17
Sandy Loam	0.4	0.33	0.29	0.24	0.2
Loamy Sand	0.5	0.36	0.3	0.26	0.22
Sand	0.6	0.4	0.35	0.3	0.25

(1) As taken from the IA-CLIA Training Manual Table Pg. 73 (September, 2004)

Access the valve run time monitors to determine the run times per valve as specified by the manufacturer's system. Use the run times, the specified precipitation rate, and application efficiency to calculate the net application. Develop a moisture balance calculation assuming the calculation starts with a one-half full root zone. Continue the calculation for a time period long enough to demonstrate the controller's ability to adequately meet a range of climatic conditions. Accumulate surplus and deficit values during the evaluation period and express as system adequacy and efficiency.

The Maximum Runtime allowable before runoff occurs will be calculated from the following formula:

$$Rt_{(max)} = 60 (ASA)/(PR - IR), \text{ minutes}$$

All time in excess of $Rt_{(max)}$ will be accumulated, converted to inches of water and logged as runoff. It will also affect system adequacy and efficiency characterizations.

The required minimum soak time between the starting of consecutive irrigation cycles will be calculated by dividing the design application (Da) by the basic soil intake rate (IR). Soak times less than the required minimum will result in runoff and be accounted for in a lower scheduling efficiency value and system adequacy.

4.4 Related Considerations

Avoid irrigating during electrical peak use periods as defined by utility servicing the location represented by the weather data records.

4.5 Test Report

The moisture balance by zones for each manufacturer's controller will be developed. Total deficit and surplus for each zone will be calculated. The magnitude of the deficit will suggest an effect on the quality of the vegetation. The magnitude of the surplus will impact the scheduling and overall efficiency. The total accumulated amount by which the actual free water exceeded the allowable value will be determined as a

measure of run-off potential. In the calculation of the moisture balance, the protocol credits rainfall before accounting for the irrigation contribution.

4.6 Test Duration

In addition to testing to the parameters given in Table 1 of the protocol, performance results are only valid if the controller must make adjustments for varying weather conditions relative to evapotranspiration and rainfall. Therefore actual time undergoing testing may be longer than one month. Valid performance data is then downloaded from the 30 consecutive day period of testing exhibiting a minimum of 0.40 in. of gross rainfall and a minimum of 2.50 in. of ETo.

4.7 Weather Data Source

The testing agency and the controller manufacturer shall mutually agree on an accredited weather data source to be used in the evaluation. The protocol uses weather source data available on a daily basis.

Note: SWAT Committee to study and define the term “accredited.”

4.8 Onsite Weather Collection Devices

When controllers use on-site weather collection devices, the protocol uses data obtained from CIMIS Station 80, located approximately ½ mile northwest of the test site.

5.0 Normative Annex

5.1 Moisture Balance and Run-off Potential Calculation Details:

Symbols:	Definition:
ASA	Allowable surface accumulation, in.
D	Deficit crop consumptive use not satisfied by moisture from rainfall or storage, in.
Da	Design application, in.
E	Irrigation system application efficiency, %
ET _c	Turf or landscape moisture requirements, in./d
ET _o	Reference crop evapotranspiration, in./d
F _w	Free water, water applied that exceeds soil intake properties, in.
I	Gross irrigation water applied, in.
I _n	Net irrigation water applied since last moisture balance calculations, in.
IR	Basic soil intake rate, in./h
K _L	Landscape coefficient
k _c	Crop (turf) coefficient
k _d	Density factor
k _{mc}	Microclimate factor
k _s	Species factor
MB	Daily calculation of root zone moisture balance, in.
MBo	Beginning daily moisture balance, in.
PR	Precipitation rate, in./h
R	Gross amount of daily rainfall as reported, in.
R _n	Net amount of daily rainfall to be used in moisture balance calculation, in.
R _t	System runtime per cycle, min.
RZWWS	Maximum amount of moisture that can effectively be stored in the root zone, in.
S	Surplus applied irrigation water that exceeds the RZWWS capacity (surplus), in.
St	Required minimum time between the start of consecutive irrigation cycles, min.

5.2 Formulas:

Formulas:	Comment:
$ET_c = K_c (ET_o), \text{ in./d}$	Turf evapotranspiration
$ET_c = K_L (ET_o), \text{ in./d}$	Landscape evapotranspiration
$K_L = (k_s) (k_d) (k_{mc})$	Landscape coefficient
$R_N = 0.8 (R), \text{ in.}$	Allows for an arbitrary loss of 20% of the rainfall to non-uniformity and runoff
$MB = MBo + \frac{I^* (E) + 0.8 (R^{**}) - ET_c}{100}, \text{ in.}$	Daily moisture balance calculation
$D = \text{Sum of } MB < 0, \text{ in.}$	Definition of Deficit
$S = \text{Sum of } MB > RZWWS, \text{ in.}$	Definition of Surplus
$St = \frac{Da (60)}{IR}, \text{ minutes}$	Minimum soak time calculation
$Fw = \frac{Rt (PR - IR)}{60}, \text{ in.}$	Free water calculation
$Rt = \frac{Da (60)}{PR}, \text{ min.}$	Runtime calculation per cycle
$Rt_{(max)} = 60 (ASA) / (PR - IR), \text{ min.}$	Maximum allowable runtime to avoid runoff
$I = (Rt) (PR) / 60, \text{ in.}$	Gross irrigation amount calculation
$Da = (I) (E), \text{ in.}$	Net irrigation calculation

* "I" must be corrected for direct and soak runoff. It is also limited to the maximum amount of RZWWS available after allowing for rainfall storage.

** "R" is limited to the maximum amount of RZWWS available for rainfall storage.

6.0 Informative Annex

6.1 Costello, L.R.

"WUCOLS a guide to the water needs of landscape plants" University of California, Cooperative Extension, 1994

6.2 ASCE-EWRI

<http://www.kimberly.uidaho.edu/water/asceewri/>

6.3 University of California, Cooperative Extension leaflet #21493

"Estimating Water Requirements of Landscape Planting – The Landscape Coefficient Method" July, 1991

6.4 Walker, Robert E. and Gary F. Kah

"Landscape Water Management Handbook" Office of Water Conservation, Department of Water Resources, State of California, Version 3.1 September, 1987

6.5 Certified Landscape Irrigation Auditor Training Manual

The Irrigation Association. September, 2004

6.6 Glossary of Irrigation Terms

The Irrigation Association. August, 2006